

LOCATION 3936 Linwood RdCITY GastoniaBETWEEN SILVER CREEKSTREET & GREYSTONE

STREET

|                   | SIZE       | TYPE      | LENGTH     | INSTALLED       | RETIRED | RENEWED |
|-------------------|------------|-----------|------------|-----------------|---------|---------|
| MAIN TO BLDG      | <u>3/4</u> | <u>P</u>  | <u>84'</u> | <u>10-11-99</u> |         |         |
| MAIN TO PROP LINE | <u>1"</u>  | <u>"</u>  | <u>16'</u> | <u>10-11-99</u> |         |         |
| PROP LINE TO BLDG | <u>1"</u>  | <u>1"</u> | <u>72'</u> |                 |         |         |

ENTERS 3936BRANCHED INTO -TAP SIZE 1/2 PRESSURE \_\_\_\_\_ PSI \_\_\_\_\_ INCHES WC LOCATION 12' N. of C ofPRESSURE TEST @ 100 PSI FOR 4 HRS BY ETD LinwoodMAIN SIZE 4" C.I. \_\_\_\_\_ BARE STEEL \_\_\_\_\_ COATED STEEL \_\_\_\_\_ PLASTIC ☒ YEAR INSTALLED 1992DEPTH 3 FT 0 IN LOCATION \_\_\_\_\_\*A\* P/S READING P TOTAL ANODES 1# \_\_\_\_\_ 17# \_\_\_\_\_ LR # \_\_\_\_\_

REMARKS \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

## Test Station

| Reading & Location                      | Lead      | Volts    |
|---|-----------|----------|
| P/S Pipeline Lead - Red New Service     | <u>OR</u> | <u>P</u> |
| P/S Pipeline Lead - White Existing Main | <u>E</u>  |          |

